

**Amendments to the Claims:**

This listing of claims will replace all prior versions and listings of claims in the application:

**Listing of Claims:**

**Claim 1 (Currently amended):** A device for extracting ~~Device for extraction of a pin of a fixation means (2) for fixation of bone fragments (3, 4) at bone fractures,~~  
wherein the ~~fixation means (2) includes a sleeve (6) and at least one pin (7) provided in said sleeve (6),~~

wherein the ~~sleeve (6) at a front end portion (9) has at least one opening (10) in a longitudinal side thereof,~~

wherein a ~~front part (11) of the pin (7) extends, when said pin (7) is located in an operating position, out of the sleeve (6) through the opening (10) and engages bone material of one of the bone fragments (3, 4), and~~

wherein the ~~extraction device (1) is adapted to pull the pin (7) in a backwards direction relative to the sleeve (6) in order to withdraw the front part (11) of the pin (7) from bone material of one of the bone fragments (3, 4) and into the sleeve (6),~~

~~characterized in that~~

the extraction device (1) comprising ~~comprises~~ an inner extraction member (12) ~~which is connectable to a pin (7) of the fixation means (2), the pin (7),~~ an outer extraction member (13) ~~which is connectable to a sleeve (6) of the fixation means (2), the sleeve (6) and an extraction handle (14) which is rotatable relative to the outer and inner extraction members (13, 12) in order to extract the pin (7) in a direction (R) of extraction relative to the outer extraction member (13) and the sleeve (6),~~

the inner extraction member (12) being insertable into the outer extraction member (13), the outer extraction member (13) being is manually holdable in order to prevent the outer extraction member (13) from rotating when the extraction handle (14) is rotated,

the outer and inner extraction members (13, 12) being respectively are provided with rotary preventing members (32, 29), ~~which cooperate~~ cooperating with each other in order to prevent the inner extraction member (12) from rotating relative to the outer extraction member (13),

the rotary preventing members (32) of the outer extraction member (13) being ~~are~~ non-circular parts of a through hole (33) in the outer extraction member (13), ~~and~~ the rotary preventing members (29) of the inner extraction member (12) being ~~are~~ non-circular parts.

**Claim 2 (Canceled)**

**Claim 3 (Previously Presented):** Device according to claim 1, characterized in that

the rotary preventing members (32) of the outer extraction member (13) are provided in a rear end portion (31) of the outer extraction member (13), and

the rotary preventing members (29) of the inner extraction member (12) are provided on a rear end portion (24) of the inner extraction member (12).

**Claim 4 (Currently amended):** Device according to claim 3, characterized in that the lengths of the inner and outer extraction members (12, 13) and the location and shape of the rotary preventing members (29, 32) are chosen such that the extraction handle (14) can cooperate with the inner extraction member (12) ~~only~~ in order to draw the ~~said~~ inner extraction member (12) backwards in the direction of extraction (R) only when said inner extraction member (12) is inserted into the outer extraction member (13) so that the rotary preventing members (29, 32) cooperate with each other.

**Claim 5 (Currently Amended):** Device according to claim 1, characterized in that at least one part (26 and/or 23) limiting the extraction is provided in order to ensure that the extraction handle (14), through the inner extraction member (12), can draw the pin (7) backwards relative to the sleeve (6) so that a tip (35) of the pin (7) is situated in an ~~the~~ opening (10) of the sleeve (6), and can thereby cooperate with a rear edge of the opening (10) such that the pin (7), through said cooperation with the rear edge of the opening (10), can draw the sleeve (6) backwards in the direction of extraction (R) when the sleeve (6) is pulled out of the bone fragment (3, 4) by means of the extraction handle (14).

**Claim 6 (Currently amended):** Device according to claim 5, characterized in that the ~~said~~ extraction limiting part (26 and/or 23) comprises one of said outer threads (26) of the extraction handle (14) and inner threads (23) of the inner extraction member (12) having such length that the length of screwing together of the outer threads (26) of the extraction handle (14) and the inner threads (23) of the inner extraction member (12) is limited.

**Claim 7 (Currently amended):** Device according to claim 1, characterized in that

~~a rear part (18) of the pin (7) has outer threads (17),~~

a front end portion (15) of the inner extraction member (12) has a hole with inner threads (16) which mesh with the outer threads (17) of the pin (7), and

the hole of the inner extraction member (12) has an inlet (22) without threads, the said inlet (22) tapering conically in a direction inwards into the hole.  
~~hole, and/or the rear part (18) of the pin (7) has an outer portion without threads, the said outer portion having a conically increasing diameter in a direction towards the outer threads (17) of the rear part (18).~~

**Claim 8 (Previously Presented):** Device according to claim 1, characterized in that the inner extraction member (12) has a front end portion (15) with such outer dimensions that it can be inserted into a rear end portion (8) of the sleeve (6).

**Claim 9 (Previously presented):** Device according to claim 8, characterized in that the front end portion (15) of the inner extraction member (12), which can be inserted into a rear end portion (8) of the sleeve (6), transforms into inner portions (20) of the inner extraction member (12) having larger outer dimensions through an edge (19) which can engage a rear edge (21) of the sleeve (6) when the inner extraction member (12) is operating.

**Claim 10 (Previously Presented):** Device according to claim 1, characterized in that

the inner extraction member (12) is an elongated rod and has a front end portion (15) with a hole which is provided with inner threads (16) which mesh with outer threads (17) on the pin (7),

the inner extraction member (12) has a rear end portion (24) with a hole with inner threads (23) which mesh with outer threads (26) on the extraction handle (14),

the outer extraction member (13) is an elongated sleeve which is open at both ends, and

the inner extraction member (12) fits into the outer extraction member and is axially displaceable in relation thereto.

**Claim 11 (Currently Amended):** Device according to claim 10, characterized in that the inner extraction member (12) includes lateral holes (36, 37) which extend into the holes with the inner threads (16, 23) such that the ~~said~~ holes can be flushed clean through the ~~said~~ lateral holes (36, 37).

**Claim 12 (Currently amended):** Device according to claim 1, characterized in that the outer extraction member (13) has a laterally directed handle (34) for holding the ~~said~~ outer extraction member (13) such that it does not rotate when the pin (7) is drawn in the direction of extraction (R).

**Claim 13 (Previously Presented):** Device according to claim 1, characterized in that the device consists of only an inner extraction member (12), an outer extraction member (13) and an extraction handle (14).

**Claim 14 (Currently Amended):** Device according to claim 1, characterized in that

the opening (10) in the sleeve (6) is round or oval or substantially round or oval, and

the front part (11) of the pin (7) has a rounded side by means of which it can cooperate with front parts of an ~~the~~ opening (10) in the sleeve (6), and another side, opposite to said rounded side, which is flat or substantially flat and which can cooperate with rear parts of the opening (10).

**Claims 15-16 (Canceled)**